Commercial Product Name: Multi Silicone DMS



Replaces version from: 30.03.2017

Print date: 15.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Revision Date: 15.11.2019

Version: 3/en

Commercial Product Name Multi Silicone DMS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Sealing of seams between tiles and materials made of glass and porce-

> lain. Connection joints in kitchen areas (e.g. around stainless sinks). Glazing of wood and aluminium windows. Seams of glass cabinets and glass

bricks.

1.3 Details of the supplier of the safety data sheet

Company designation fischerwerke GmbH & Co. KG

> Klaus-Fischer-Straße 1 D-72178 Waldachtal

Telephone: +49(0)7443 12-0 FAX: +49(0)7443 12-4222 Email: info-sdb@fischer.de Internet: www.fischer.de

Marketer Great Britain: Mrs Mirka Valovicova, fischer Fixing (UK) Ltd

Hithercroft Road

Wallingford, Oxfordshire, OX10 9AT Telephone: +44 01491 827 920

FAX: +44 01491 827 950 Internet: www.fischer.co.uk

1.4 Emergency telephone number

Emergency telephone number +49(0)6132-84463 (24h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regula- This product is classified as not hazardous according to regulation (EC)

tion (EC) No. 1272/2008

1272/2008 [CLP].

2.2 Label elements

Labelling according to Regulation

(EC) No. 1272/2008 [CLP]

The product does not have to be labelled according to Regulation (EC)

No. 1272/2008 [CLP].

Further information EUH208: Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one. May produce

an allergic reaction.

EUH210: Safety data sheet available on request.

Commercial Product Name: Multi Silicone DMS



Replaces version from: 30.03.2017

Print date: 15.11.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Version: 3/en

Hazardous ingredients

Revision Date: 15.11.2019

Ingredient	CAS No.	Classification (EC) 1272/2008	Concentration
Distillates (petroleum), hydrotreated middle	*EC-No.: 934-956-3 REACH No.: 01-2119827000-58	*Asp. Tox. 1; H304	20.0 - 25.0 % by weight
Distillates (petroleum), hydro-treated light predominantly in the range of C9 through C16 and boiling in the range of approximately 150 oC to 290 oC (302 oF to 554 oF).]	*CAS No.: 64742-47-8 EC-No.: 265-149-8 Index-No.: 649-422-00-2 *REACH No.: 01-2119484819-18	*Asp. Tox. 1; H304	5.0 - 10.0 % by weight
4,5-dichloro-2-octyl-2H-isothiazol-3-one	CAS No.: 64359-81-5 *EC-No.: 264-843-8	Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 4; H312Skin Corr. 1C; H314 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0.0015 % by weight

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice If symptoms persist, call a physician.

Remove/Take off immediately all contaminated clothing.

If inhaled IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

In case of skin contact IF ON SKIN: Gently wash with plenty of soap and water.

plenty of water, also under the eyelids, for at least 15 minutes.

If swallowed, seek medical advice immediately and show this container or

label.

Clean mouth with water and drink afterwards plenty of water. Drink 1 or

2 glasses of water.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No data available

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention No data available
Special medical treatment No data available

Commercial Product Name: Multi Silicone DMS

fischer winnovative solutions

Replaces version from: 30.03.2017

Print date: 15.11.2019

SECTION 5: Firefighting measures

5.1 Extinguishing media

Revision Date: 15.11.2019

Version: 3/en

Suitable extinguishing media Carbon dioxide (CO2)

Dry powder

Foam

Water spray jet

Extinguishing media which must not be used for safety reasons

High volume water jet

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or prepara-

tion itself, its combustion products, or released gases Heating or fire can release toxic gas.

5.3 Advice for firefighters

Special protective equipment for

firefighting

In the event of fire, wear self-contained breathing apparatus. In the event of fire and/or explosion do not breathe fumes.

Additional information on fire-

fighting

Fire residues and contaminated fire extinguishing water must be dis-

posed of in accordance with local regulations.

Keep containers and surroundings cool with water spray. Container may

rupture on heating.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Environmental precautions The product should not be allowed to enter drains, water courses or the

soil.

Prevent spreading over a wide area (e.g. by containment or oil barriers).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Use mechanical handling equipment.

Treat recovered material as described in the section "Disposal considera-

tions".

6.4 Reference to other sections

Reference to other sections See chapter 8/13

Commercial Product Name: Multi Silicone DMS



Replaces version from: 30.03.2017

Print date: 15.11.2019

6.5 Additional information

Revision Date: 15.11.2019

Version: 3/en

Other information Dispose of in accordance with local regulations.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling None under normal processing.

Advice on protection against fire

ire

No special precautions required.

and explosion

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re- Kee

quirements

Keep containers tightly closed in a cool, well-ventilated place.

Store in accordance with local regulations.

Keep only in original container.

Hints on storage assembly Store in accordance with the particular national regulations.

German storage class 10-13 (TRGS 510)

7.3 Specific end use(s)

Specific use(s) Sealant

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

8.2 Exposure controls

Respiratory protection No personal respiratory protective equipment normally required.

Hand protection not required under normal use

Suitable material butyl-rubber, Chloroprene, Nitrile rubber

Unsuitable material PVC disposable gloves

Material thickness adjust to application and duration of use

Break through time adjust to application and duration of use

Remarks Replace when worn. Request information on glove permeation proper-

ties from the glove supplier. Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous out-

side influences (e.g. temperature).

Eye protection Tightly fitting safety goggles

Commercial Product Name: Multi Silicone DMS



Replaces version from: 30.03.2017

Print date: 15.11.2019

Skin and body protection Wear suitable protective equipment.

Note Choose body protection according to the amount and concentration of

the dangerous substance at the work place.

General protective and hygiene

Revision Date: 15.11.2019

measures

Version: 3/en

Smoking, eating and drinking should be prohibited in the application

area.

Avoid contact with skin, eyes and clothing.

Take off all contaminated clothing immediately.

Wash hands before breaks and at the end of workday.

Keep away from food, drink and animal feedingstuffs.

Use protective skin cream before handling the product.

Information on environmental

protection regulations

No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form paste

Colour various

Additional information on

colour

see label

Odour of vinegar

pH not determined

Melting point [°C] / Freezing point not d

[°C]

not determined

Boiling point [°C] not determined

*Flash point [°C] not applicable

Explosion limits [Vol-%]

Lower limit not determined

Upper limit not determined

Vapour pressure [kPa] not determined

*Density [g/cm³] 0,96

Water solubility [g/l] insoluble

Autoinflammability not auto-flammable

*Viscosity, dynamic [kg/(m*s)] 800

Risk of explosion. not explosive.

9.2 Other information

*Ignition temperature [°C] 400

Commercial Product Name: Multi Silicone DMS



Replaces version from: 30.03.2017

Print date: 15.11.2019

*Solvent content [%] < 3

*Solid content [%] not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

Thermal decomposition No decomposition if stored and applied as directed.

10.2 Chemical stability

Revision Date: 15.11.2019

Version: 3/en

Chemical stability Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid None known.

10.6 Hazardous decomposition products

Hazardous decomposition prod- No decomposition if used as directed.

ucts

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Oral toxicity [mg/kg]

Hazardous ingredients

Distillates (petroleum), hydrotreated middle				
Value	Test criterion	Test species	Source	
> 2000	LD50	rat	Company data	

Distillates (petroleum), hydro- treated light predominantly in the range of C9 through C16 and boiling in the range of approxi mately 150 oC to 290 oC (302 oF to 554 oF).]					
Value	Value Test criterion Source				
> 15000	LD50	Company data			

Dermal toxicity [mg/kg]

Hazardous ingredients

Distillates (petroleum), hydrotreated middle				
Value	Test criterion	Test species	Source	
> 2000	LD50	rabbit	Company data	

Commercial Product Name: Multi Silicone DMS



Replaces version from: 30.03.2017

Print date: 15.11.2019

Distillates (petroleum), hydro- treated light predominantly in the range of C9 through C16 and boiling					
in the range of approxi mately 150 oC to 290 oC (302 oF to 554 oF).]					
Value	Tost critorion	Cource			

value	rest criterion	Source	
> 3160	LD50	Company data	

Inhalative toxicity [mg/l]

Revision Date: 15.11.2019

Version: 3/en

Hazardous ingredients

Distillates (petroleum), hydrotreated middle				
Value	Test criterion	Test species	Exposure dura- tion	Source
> 5266	LC50	rat	4 h	Company data

Irritant effect on skin No skin irritation

Irritant effect on eyes No eye irritation

Sensitization No known effect.

11.2 Additional information

Other information (chapter 11.) There is no data available for this product.

SECTION 12: Ecological information

12.2 Persistence and degradability

Biodegradability

Remarks No data available

12.3 Bioaccumulative potential

Bioaccumulation no data available

12.4 Mobility in soil

Mobility

termination

Mobility No data available

12.5 Results of PBT and vPvB assessment

Results of PBT characteristics de-

This preparation contains no substance considered to be persistent,

bioaccumulating nor toxic (PBT).

12.6 Other adverse effects

Further information on ecology No information on ecology is available.

Commercial Product Name: Multi Silicone DMS



Replaces version from: 30.03.2017

Print date: 15.11.2019

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Revision Date: 15.11.2019

Version: 3/en

Disposal considerations Disposal together with normal waste is not allowed. Special disposal re-

quired according to local regulations.

The product should not be allowed to enter drains, water courses or the

soil.

Empty remaining contents.

Waste Code **Product**

200127 - paint, inks, adhesives and resins containing dangerous sub-

stances

080000 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS

ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

080400 - wastes from MFSU of adhesives and sealants (including water-

proofing products)

080409 - waste adhesives and sealants containing organic solvents or

other dangerous substances

cured material

200000 - MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING

SEPARATELY COLLECTED FRACTIONS

Uncleaned empty packaging Dispose of as unused product.

SECTION 14: Transport information

	*Land transport ADR/RID	*Marine transport IMDG	*Air transport ICAO/IATA
14.1 UN-No	Not applicable.	Not applicable.	Not applicable.
14.2 Description of the	No dangerous good accord-	No dangerous good accord-	No dangerous good accord-
goods	ing to ADR	ing to IMDG	ing to IATA
14.3 Transport hazard	Not applicable.	Not applicable.	Not applicable.
class(es)			
14.4 Packaging group	Not applicable.	Not applicable.	Not applicable.
14.5 Environmental hazards	Not applicable.	Not applicable.	Not applicable.
UN proper shipping name		Non dangerous good	Non dangerous good

14.6 Special precautions for user

Precautions not required under normal use

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL and the IBC not applicable

Code

Commercial Product Name: Multi Silicone DMS



Replaces version from: 30.03.2017

Print date: 15.11.2019

14.8 Additional information

Revision Date: 15.11.2019

Version: 3/en

Other information (chapter 14.) Not dangerous goods in the meaning of ADR/RID, ADNR, IMDG-Code,

ICAO/IATA-DGR

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

*Water Hazard Class (Ger.) 2

15.2 Chemical safety assessment

Safety assessment Not relevant. Chemical safety assessments for substances in this mixture

were not carried out.

*Additional regulations This product is a "Treated article without primary biocidal function (Art.

58 in conjunction with Art. 3 (1) a))". This product protects itself by the added film protection active substance, which cannot show any outwardly directed effect by the resulting plastic film. Film protective agent: 4,5-

dichloro-2-octyl-2H-isothiazol-3-one

SECTION 16: Other information

Modifications since last version Modifications of the previous version are denoted with an asterisk (*).

Relevant H-phrases H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways. H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H330: Fatal if inhaled.

H335: May cause respiratory irritation.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

EUH208: Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one. May produce

an allergic reaction.

Wording of the hazard classes Asp. Tox.: Aspiration hazard

Acute Tox.: Acute toxicity Skin Sens.: Skin sensitization

STOT SE: Specific target organ toxicity - single exposure Aquatic Acute: Hazardous to the aquatic environment Aquatic Chronic: Hazardous to the aquatic environment

This product is classified as not hazardous according to regulation EC CLP

Modifications of the previous version are denoted with an asterisk (*).

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.